

## SPECIFICATIONS

L.O.A : 10.60 m  
Length of hull : 9.80 m  
Width of hull : 3.15 m  
Weight : 3 600 kg  
Draft : 0.45 m  
Minimum air draught on sea : 2,50 m  
Fuel tank capacity : 480 l  
Water tank capacity : 95 l  
Engine : single or twin-engined diesel  
Maximum engine power single engine : 370 HP  
Maximum engine power twin-engined : 2 x 260 HP  
Transmission : hydrojet or Z-drive  
EC certification : B8 - C14  
Architects : Joubert-Nivelt  
Designer : Bertrand Danglade

## STANDARD EQUIPMENT

### Construction

Hull bottom : balsa sandwich  
Deck: 12 mm marine ply sandwich  
Hull and deck reinforced polyester laminate  
Teak capping on gunwale  
Teak deck  
Teak bulwark

### Cockpit and deck

Self-draining cockpit  
Self-draining anchor locker  
Folding stem head anchor roller  
Electric anchor windlass  
2 fairleads fore  
2 mooring cleats fore and aft  
2 spring cleats  
Stainless steel grab rail on each skin  
Seating area forward for 8 person with removable table  
3 lockers below forward seating  
3-seat fore banquette with 2 stainless steel hand-rail  
Sun bed aft converts to seating for 5 with back-rests  
2 teak glasses support  
1 locker aft

Galley with 1burner cooker, sink, storage lockers  
65-litre fridge  
Deck shower  
95-litre fresh water tank  
Stainless steel and teak bathing platform with bathing ladder  
Stainless steel flagpole  
Eyelets for fenders  
Manual bilge pump

### Steering position

Seats for driver and co-pilot adjustable  
Windscreen  
5 stainless steel handrails  
Stainless steel mast for navigational lights  
Engine controls  
Engine instrument panel  
Instrument console  
Compass  
Hydraulic steering wheel  
Teak documents stowage  
2 stainless steel glass stowage

### Cabin

Double berth  
Storage lockers  
4 opening portholes  
Head : marine toilet and washbasin  
Holding tank

### Engine facilities

Diesel single or twin-engined  
Waterjet or stern drive transmission  
480-litre aluminum fuel tank  
Soundproofing in engine compartment  
Electrically operated engine cover

### Electrical Equipment

3 x 12 volt, 105 amp battery. Single engine  
4x 12 volt, 105 amp battery. Twin-engined  
Electrical distribution panel with 12v socket and circuit breaker  
Lighting in cabin and toilet  
Navigation lights  
Bilge pump